

BRACKETT AIR FILTERS

INSTRUCTIONS

ASSEMBLY PART NO. BA-120 Dwr. No. 8994656

APPROVED ON AIRCRAFT MODELS: SEE FAA APPROVED
APPLICABILITY LIST

REPLACES: 55025-501, CA146PL, A134C.

FAA APPROVAL DATA: STC-SA693CE List No. 1
FAA-PMA Supplement No. 1

Your new polyurethane air filter element has been designed to give maximum dust collecting efficiency, good air flow, lightweight, and economical replacement. The element has been treated with a special treatment called a wetted agent and is approximately 98% efficient. The special wetted agent is the secret to the efficiency of capturing dust and repelling water. The element has also been treated with a fire retardant. For the above reasons, replace the element each 200 hours of use or every 12 months or when 50% covered with foreign material. DO NOT WASH AND REUSE.

INSTALLATION INSTRUCTIONS

- Step 1. Install filter using the same procedure as with the original filter.
- Step 2. Apply service decal to the filter canister. PLACE SO IT IS READABLE.
- Step 3. NOTE: After initial installation of filter assembly fill out FAA Form 337 for return to service. On future replacement of parts this form will not be required.

SERVICING: Under normal conditions, replace filter element, PN BA-20, after 200 hours use or 1 year intervals. Under severely dusty conditions, check daily and replace when element is 50% covered with foreign material.

Instruction Sheet
Part No. BA-120-3
Date: Rev. 8-23-88